```
Oliebitin mež. 189039
Gul legi Os28-577605 - nimal i iceli Kevin
```

What is claimed is:

- 1. A plastic substrate for organic electroluminescent
 2 devices, comprising:
- 3 a plastic substrate; and
- 4 a deposition film with a predetermined thickness formed 5 on the plastic substrate by plasma chemical vapor deposition, the film having a formula 6 7 $SiO_eC_aH_bX_cY_dZ_f$ (e\leq 2, 2-e=a+b+c+d+f), wherein X, Y 8 and Z are selected form the group consisting of 9 Sc, Ti, V, Cr, Mn, Fe, Co, Ni, Cu, Zn, Pd, Ag, Pt, Au and the elements in periodic table 3 0]] IA, IIA, IIIA, IVA, VA, VIA and VIIA 12 excepting H.
- 2. The plastic substrate for organic electroluminescent devices as claimed in claim 1, wherein the predetermined thickness is 0.1 to 4.5 µm.
- 3. A fabrication method for a plastic substrate for organic electroluminescent devices, comprising the steps of:
- 3 providing a plastic substrate; and
- performing plasma chemical vapor deposition to form a deposition film of predetermined thickness on the plastic substrate, the film having a formula of $SiO_eC_aH_bX_cY_dZ_f$ (e ≤ 2 , 2-e=a+b+c+d+f), wherein X, Y and Z are selected form the group consisting of Sc, Ti, V, Cr, Mn, Fe, Co, Ni, Cu, Zn, Pd, Ag, Pt, Au and the elements in periodic table

Client's results follo Our wat: 6828 8778097 final/ loa/ Movin

- IA, IIA, IIIA, IVA, VA, VIA and VIIA 11
- 12 excepting H.
 - 1 substrate for organic The plastic
 - electroluminescent devices as claimed in claim 3, wherein
 - the predetermined thickness is 0.1 to 4.5 µm.
- 1 5. An organic electroluminescent device, comprising:
- 2 a cathode;
- 3 an anode;
- 4 at least an organic layer between the anode and the
- 5 cathode, such that when a voltage is applied to
- 6 the cathode and the anode, the organic layer
- 7 electroluminesces;
- 8 a first plastic substrate beneath the cathode; and
- a second plastic substrate as claimed in claim 1 above
- 1.0 the anode.